

## LEGRIS STAINLESS STEEL PUSH-IN MALE ELBOW



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/23/2026 08:50 PM

SKU

: 4004

BRAND

: DIXON VALVE

MODEL

: 38896018

Applications:

Suitable for many industries such as: chemical, food, packaging and medical

Use:

Compatible with a range of tubes including: semi-rigid nylon tube, flexible polyurethane tube, low density polyethylene, PTFE tube FEP 140, stainless steel and copper tube (when grooved)

Specifications:

Materials conforming to FDA and 1934/2004 CE standards

Features:

The body is orientable for positioning purposes.

Construction:

AISI 316 stainless steel body with 316L stainless steel backup washer and 303L stainless steel collet

Silicone free

FKM O-ring

Note:

Thread sealant does not come pre-applied on male threads, allowing the appropriate sealant for the application to be applied by the user.

Safety notes:

Maximum circuit pressure depends equally on the type and diameter of the tube used.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	38896018
<b>Male Thread</b>	NPT
<b>Male Thread Size</b>	3/8"
<b>Material</b>	Stainless Steel
<b>Maximum Operating Pressure</b>	290 PSI
<b>Seal</b>	FKM O-ring
<b>Temperature Range</b>	-4°F to 245°F (-20°C to 118°C)
<b>Tube OD</b>	3/8"
<b>Vacuum Capability</b>	28" HG
<b>Weight Lb</b>	0.1250