

**AG-SERIES AGRICULTURAL  
PUSH-PULL BALL FEMALE  
THREADED COUPLER**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 04:15 AM

SKU

: 4013

BRAND

: DIXON VALVE

MODEL

: 3AGF3-PS

Applications:

Used on construction equipment, farm implements and most other mobile equipment

Specifications:

The International Standard Organization (ISO) has adopted specifications regarding dimensions and interchangeability.

Construction:

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Steel coupler sleeves are hardened to resist deformation and maximize service life.

Nitrile (Buna-N) seals are standard

Couplers have a PTFE Anti-Extrusion ring

Ball valve and poppet valve options available

Compatibility & Interchange Data:

Pioneer Agricultural Interchange

Parker/Pioneer 4000 Series

Safeway S20

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	3/8"
<b>Factory Part Number</b>	3AGF3-PS
<b>Material</b>	Steel
<b>Seal</b>	Buna-N
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	3/8"-18