

**DQC CM-SERIES INDUSTRIAL  
MOLD INTERCHANGE  
UNVALVED COUPLER 90°  
PUSH-LOC BARB**

DATE  
: 07/08/2026 07:47 PM

SKU  
: 4034

BRAND  
: DIXON VALVE

MODEL  
: 3CM9B3-B-E



Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 14,500 PSI (1,000 bar) Burst  
Rated pressure for connected Brass Unvalved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 14,200 PSI (1,000 bar) Burst

Construction:

Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Silicone gaskets are standard

Compatibility & Interchange Data:

Mold Coolant Interchange  
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	3/8"
<b>Factory Part Number</b>	3CM9B3-B-E
<b>Hose ID</b>	3/8"
<b>Length</b>	2.93"
<b>Material</b>	Brass
<b>Maximum OD</b>	0.95"
<b>Temperature Range</b>	-90°F to +400°F (-68°C to +205°C)
<b>Weight Lb</b>	0.2500