

## DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE VALVED COUPLER HOSE BARB



DATE  
: 05/22/2026 10:39 AM

SKU  
: 4049

BRAND  
: DIXON VALVE

MODEL  
: 3CMS3-B

### Specifications:

Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,700 PSI (450 bar) Burst  
Rated pressure for connected Brass Valved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 6,100 PSI (400 bar) Burst

### Construction:

Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Silicone gaskets and valve O-rings are standard

### Compatibility & Interchange Data:

Mold Coolant Interchange  
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

### Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	3/8"
<b>Factory Part Number</b>	3CMS3-B
<b>Hose ID</b>	3/8"
<b>Length</b>	3.30"
<b>Material</b>	Brass
<b>Maximum OD</b>	0.95"
<b>Temperature Range</b>	-90°F to +400°F (-68°C to +205°C)
<b>Weight Lb</b>	0.2340