


DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE COUPLER



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 12:05 PM

SKU
: 4055

BRAND
: DIXON VALVE

MODEL
: 3CVVF3

Construction:
Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel components are plated using ROHS Compliant Trivalent Chrome.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	26000 PSI (1800 Bar)
Factory Part Number	3CVVF3
Hex	22mm
Length	2.41" (61.2mm)
Material	Steel
Maximum OD	1.34" (34.0mm)
Maximum Operating Pressure	6500 PSI (450 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF

TECHNICAL SPECIFICATIONS

Thread Size	3/8"-19
Weight Lb	0.4000