


DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 02:56 PM

SKU

: 4070

BRAND

: DIXON VALVE

MODEL

: 3EF3-S

Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Machined components are manufactured using 303 stainless steel bar stock. Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	22,000 PSI (1,517 Bar)
Factory Part Number	3EF3-S
Female Thread	NPTF
Female Thread Size	3/8"-18
Hex	1"
Length	1.60 (40.6mm)
Material	303 Stainless Steel
Maximum OD	1.12 (28.4mm)
Maximum Operating Pressure	5,500 PSI (379 Bar)
Seal	Buna-N
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.2200