


DQC E-SERIES STRAIGHT THROUGH INTERCHANGE HOSE BARB COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 05:36 PM

SKU

: 22414

BRAND

: DIXON VALVE

MODEL

: 3ES3-B

Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Machined components are manufactured using solid brass

Nitrile (Buna-N) seals are standard

Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Burst Pressure	10,800 PSI (745 Bar)
Factory Part Number	3ES3-B
Hose ID	3/8"
Length	2.03" (51.6mm)
Material	Brass
Maximum OD	1.13 (28.6mm)
Maximum Operating Pressure	2,700 PSI (186 Bar)
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.2100