

## DQC K-SERIES ISO-A INTERCHANGE FEMALE COUPLER



DATE  
: 05/23/2026 06:46 PM

SKU  
: 22455

BRAND  
: DIXON VALVE


MODEL  
: 3KF3-SS

Features:  
Poppet style shut-off valve

Construction:  
Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Steel componentry is plated using ROHS Compliant Trivalent Chrome.  
Steel coupler sleeves are hardened to resist deformation and maximize service life.  
Nitrile (Buna-N) seals are standard  
Couplers have a PTFE Anti-Extrusion ring.  
Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.

Available Options:  
Contact Dixon for all available option adders  
Standard seal options include: FKM, EPDM, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone  
Kalrez® seal options include: 4079, 6375 and 7075  
Valve options include: Unvalved, actuator, steel, brass, 303 stainless steel and 316 stainless steel  
Locking sleeve option available  
Oxy-Clean treatment is available

Compatibility & Interchange Data:  
Interchangeable to ISO7241 Series 'A'  
Parker 6600-Series, Aeroquip/Eaton FD56 (5600)  
Faster ANV, Hansen HA 15000, Safeway S56-Series



\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**Note:**

Please contact Dixon® for working pressures

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	3/8"
<b>Factory Part Number</b>	3KF3-SS
<b>Hex</b>	7/8"
<b>Length</b>	2.23" (56.6mm)
<b>Material</b>	316 Stainless Steel
<b>Maximum OD</b>	1.19" (30.2mm)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	3/8"-18
<b>Weight Lb</b>	0.3255