


## M-SERIES ARO PNEUMATIC AUTOMATIC MALE THREADED COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/23/2026 09:40 PM

SKU  
: 4112

BRAND  
: DIXON VALVE

MODEL  
: 3MM3-PL

### Specifications:

Rated pressure for connected Steel Coupler & Steel Plug: 300 PSI (20 bar)  
Maximum Working and 3,300 PSI (228 bar) Burst

### Construction:

Machined components are manufactured using solid bar stock.  
Stainless steel springs. Carbon steel balls and retaining rings.  
Nitrile (Buna-N) seals are standard  
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

### Compatibility & Interchange Data:

ARO 310  
Hansen 210/310

### Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                            |  |
|----------------------------|--|
| <b>Body Size</b>           | 3/8"                                   |
| <b>Factory Part Number</b> | 3MM3-PL                                |
| <b>Hex</b>                 | 1-1/16"                                |
| <b>Length</b>              | 1.89"                                  |
| <b>Material</b>            | Nickel Plated Brass Body, Steel Sleeve |
| <b>Maximum OD</b>          | 1.26"                                  |
| <b>Pressure Rating</b>     | See Product Details                    |
| <b>Temperature Range</b>   | -40°F to +250°F (-40°C to +121°C)      |
| <b>Thread</b>              | NPT                                    |
| <b>Thread Size</b>         | 3/8"                                   |
| <b>Weight Lb</b>           | 0.3800                                 |