

CAM & GROOVE ADAPTER X NPSM THREAD



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 01:13 PM

SKU

: 4247

BRAND

: DIXON VALVE

MODEL

: 400-AS-AL

Applications:

Designed for the delivery of dry goods

Specifications:

Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Construction:

Cork Buna gasket in threaded end

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Note:

Replacement gasket is available part # 400GAGFI

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating is based on the seal of the mating part

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	356T6 Aluminum
Maximum Operating Pressure	100 PSI
Factory Part Number	400-AS-AL
Size	4"
Weight Lb	1.6600