

DIXON® CAM & GROOVE TYPE F ADAPTER X MALE NPT



DATE
: 06/13/2026 08:17 PM

SKU
: 4292

BRAND
: DIXON VALVE

MODEL
: 400-F-SS


Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item
Description A-A-59326D

How it works:
To make a connection, simply slide the adapter into the coupler and with
normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and
remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for
compressed air or steam service!
Pressure rating is based on the seal of the mating part
Pressure rating recommendations are based on the use of mating Dixon
fittings at ambient temperature 70°F / 21°C with a standard seal installed. For
use at elevated temperature or other unusual operating conditions, consult
Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	400-F-SS
Material	316 Stainless Steel
Maximum Operating Pressure	100 PSI
Size	4"
Weight Lb	7.1600