

CAM & GROOVE 22½° COUPLER X TTMA FLANGE

DATE
: 07/08/2026 07:17 AM

SKU
: 4314

BRAND
: DIXON VALVE

MODEL
: 4002DLTAL

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item
Description A-A-59326D

Construction:
Buna-N gasket

Available Options:
Other gasket types are available, contact Dixon.

How it works:
To make a connection, simply slide the adapter into the coupler and with
normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and
remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for
compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon
fittings at ambient temperature 70°F (21°C) with a standard seal installed. For
use at elevated temperature or other unusual operating conditions, consult
Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|----------------|
| Material | 356T6 Aluminum |
| Maximum Operating Pressure | 100 PSI |
| Factory Part Number | 40022DLTAL |
| Seal | Buna-N |
| Size | 4" |
| Weight Lb | 3.1050 |