

BAYCO HIGH FLOW SERIES SWING CHECK VALVE FEMALE NPT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 12:13 PM

SKU

: 4407

BRAND

: DIXON VALVE

MODEL

: 4042TE

Applications:

Often used on both the blower and trailer, designed to prevent product backflow if a product line should become plugged.

Use:

When in use the flapper can swing completely out of the air path, resulting in increased air flow and subsequently increased product flow.

Complete repairs can easily be carried out on all high flow swing check valves without removing from the tank.

Features:

Flapper return springs are standard

Huck bolted flapper assembly prevents loose parts from contaminating the product.

Construction:

Aluminum body and inspection lid

Stainless steel hardware

All white EPDM & silicone seals are compliant with FDA

Safety notes:

Inspection lids can be removed to facilitate routine flapper assembly inspections (system must not be in service during inspections or repair.)

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Female Thread	NPT
Female Thread Size	4"
Includes	Flapper return springs
Length	9"
Material	Aluminum
Factory Part Number	4042TE
Seal	White silicone
Temperature Rating	400°F (204°C)
Weight Lb	9.5200