

## TYPE AA ADAPTER X ADAPTER



DATE  
: 06/16/2026 09:02 AM

SKU  
: 4422

BRAND  
: DIXON VALVE

MODEL  
: 4060-AA-SS

**Applications:**

Designed for use with liquids, consult Dixon for specific recommendations

**Specifications:**

Produced to interchange with all product produced to Commercial Item Description A-A-59326D

**Construction:**

Produced as a welded fabrication

**How it works:**

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

**Safety notes:**

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating is based on the seal of the mating part

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Material</b>	316 Stainless Steel
<b>Maximum Operating Pressure</b>	75 PSI
<b>Factory Part Number</b>	4060-AA-SS
<b>Size</b>	4" x 6" (100mm x 150mm)
<b>Weight Lb</b>	6.0000