

HEAVY DUTY BUTTERFLY VALVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/02/2026 04:21 PM

SKU
: 27149

BRAND
: DIXON VALVE

MODEL
: 4BF416DITF-CNBR

Applications:

Low-pressure transfer of water, acids, chemicals, slurries, and other liquids
Designed for all low-pressure hydraulic fracturing applications

Features:

Locator notches around the outer edge of the body allow the valve to easily line up at center

Actuator mounting flange outfitted with both industry standard and ISO bolt circle diameters

Thicker stems deliver a more durable and reliable performance

Grease zerk added to body neck for reliable performance

10-position throttling handle for controlled accuracy

For use between lightweight flanges: 125 lb., 150 lb., or butterfly valve flange

Valve is rebuildable, contact Dixon for replacement parts

Note:

Dixon provides actuation services for industrial and sanitary valves.

Halliburton SAP# 100001149

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Valve with Buna-N seat
Material	Body: ductile iron, Disc: nickel-plated ductile iron, Bushings: PTFE, O-rings: Buna-N, Stems: 416 stainless steel, Retaining pins: stainless steel, Handle: malleable iron
Maximum Operating Pressure	200 PSI

TECHNICAL SPECIFICATIONS

Factory Part Number	4BF416DITF-CNBR
Seat	Buna-N or FKM
Size	4"
Temperature Range	Buna-N seat -20°F to 200°F , FKM seat 0°F to 200°F (Buna-N seat -28°C to 93°C, FKM seat -17°C to 93°C)