

HEAVY DUTY BUTTERFLY VALVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/02/2026 04:22 PM

SKU
: 27150

BRAND
: DIXON VALVE

MODEL
: 4BF416DITF-FKM

Applications:

Low pressure transfer of water, acids, chemicals, slurries and other liquids

Designed for all low pressure hydraulic fracturing applications

Specifications:

Typical gauge pressures in transfer applications range from 50 to 200 PSI working pressure (MSS SP-67 spec)

Features:

Locators around the outer edge of the body allow the valve to easily line up at center

Thicker stems compared to other brands delivers a more durable and reliable performance

Grease zerk added to body neck for reliable performance

10-position throttling handle for control accuracy

For use between two lightweight, 125 lb., or 150 lb. valve flanges

Construction:

Disc: Nickel plated ductile iron with Buna-N seat (0°F to 200°F), or FKM seat (0°F to 200°F)

Bushings: PTFE

O-rings: Buna N

Stems: 416 stainless steel

Retainer pins: 304 stainless steel

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Valve with FKM seat
Material	Body: ductile iron
Factory Part Number	4BF416DITF-FKM
Size	4"
Weight Lb	13.6000
Working Pressure	200 PSI