

## HEAVY DUTY BUTTERFLY VALVE

DATE  
: 05/02/2026 04:22 PM

SKU  
: 27151

BRAND  
: DIXON VALVE

MODEL  
: 4BF416DITF-NBR



### Applications:

Low pressure transfer of water, acids, chemicals, slurries and other liquids  
Designed for all low pressure hydraulic fracturing applications

### Specifications:

Typical gauge pressures in transfer applications range from 50 to 200 PSI  
working pressure (MSS SP-67 spec)

### Features:

Locators around the outer edge of the body allow the valve to easily line up at center

Thicker stems compared to other brands delivers a more durable and reliable performance

Grease zerk added to body neck for reliable performance

10-position throttling handle for control accuracy

For use between two lightweight, 125 lb., or 150 lb. valve flanges

### Construction:

Disc: Nickel plated ductile iron with Buna-N seat (0°F to 200°F), or FKM seat (0°F to 200°F)

Bushings: PTFE

O-rings: Buna N

Stems: 416 stainless steel

Retainer pins: 304 stainless steel

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Description</b>	Valve with Buna-N seat
<b>Material</b>	Body: Ductile iron
<b>Factory Part Number</b>	4BF416DITF-NBR
<b>Size</b>	4"
<b>Weight Lb</b>	13.6000
<b>Working Pressure</b>	200 PSI