

**DQC CM-SERIES INDUSTRIAL  
MOLD INTERCHANGE  
UNVALVED COUPLER 45°  
PUSH-LOC BARB**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 06:56 PM

SKU  
: 4866

BRAND  
: DIXON VALVE

MODEL  
: 4CM4B6-B-E

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:

Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Silicone gaskets are standard

Compatibility & Interchange Data:

Mold Coolant Interchange  
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	4CM4B6-B-E
<b>Hose ID</b>	3/4"
<b>Length</b>	4.56"
<b>Material</b>	Brass
<b>Maximum OD</b>	1.18"

**TECHNICAL SPECIFICATIONS**

**Temperature Range** -90°F to +400°F (-68°C to +205°C)