

**DQC CM-SERIES INDUSTRIAL
MOLD INTERCHANGE
UNVALVED COUPLER 90°
PUSH-LOC BARB**



DATE
: 05/22/2026 08:56 AM

SKU
: 4869

BRAND
: DIXON VALVE

MODEL
: 4CM9B4-B-E

Specifications:

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

Construction:

Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Silicone gaskets are standard

Compatibility & Interchange Data:

Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|------------|
| Body Size | 1/2" |
| Factory Part Number | 4CM9B4-B-E |
| Hose ID | 1/2" |
| Length | 3.50" |
| Material | Brass |
| Maximum OD | 1.18" |

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|--------------------------|-----------------------------------|
| Temperature Range | -90°F to +400°F (-68°C to +205°C) |
| Weight Lb | 0.4700 |