


**DQC CM-SERIES INDUSTRIAL  
MOLD INTERCHANGE  
UNVALVED COUPLER HOSE  
BARB**

DATE  
: 07/08/2026 07:39 PM

SKU  
: 4877

BRAND  
: DIXON VALVE

MODEL  
: 4CMS4-B-E



**Specifications:**

Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 4,900 PSI (340 bar) Burst

**Construction:**

Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Silicone gaskets are standard

**Compatibility & Interchange Data:**

Mold Coolant Interchange  
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

**Safety notes:**

Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	4CMS4-B-E
<b>Hose ID</b>	1/2"
<b>Length</b>	2.98"
<b>Material</b>	Brass
<b>Maximum OD</b>	1.18"

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Temperature Range</b>	-90°F to +400°F (-68°C to +205°C)
<b>Weight Lb</b>	0.4200