


**DQC CVV-SERIES EUROPEAN  
INTERCHANGE FEMALE  
COUPLER**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 10:49 PM

SKU  
: 4883

BRAND  
: DIXON VALVE

MODEL  
: 4CVVFM2215

Construction:

Machined components are manufactured using solid bar stock

Steel retaining rings and springs maximize service life in rugged environments.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:

European Screw-Together Interchange

Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Note:

Threaded sleeves enable easy connection and disconnection while system is under residual pressure only.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	1/2"
<b>Burst Pressure</b>	23200 PSI (1600 Bar)
<b>Factory Part Number</b>	4CVVFM2215
<b>Hex</b>	27mm
<b>Length</b>	2.66" (67.5mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	1.65" (41.8mm)

## TECHNICAL SPECIFICATIONS

<b>Maximum Operating Pressure</b>	5800 PSI (400 Bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female Metric
<b>Thread Size</b>	M22X1.5
<b>Weight Lb</b>	0.5500