

DQC EA-SERIES WATER-BLAST INTERCHANGE COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 06:29 AM

SKU
: 4899

BRAND
: DIXON VALVE

MODEL
: 4EAF4

Construction:

Machined components are manufactured using solid high strength steel bar stock.

Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.

Latches are manufactured from high-strength steel and plated with electroless nickel.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nitrile (Buna-N) seals are standard

Couplers have a PTFE Anti-Extrusion ring to prevent O-Ring dynamic impulse pressure damage

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, FDA FKM, Mil-Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Compatibility & Interchange Data:

Water-Blast Interchange

Parker Series-WB, Aeroquip FD69, Snap-Tite 56-Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1/2" |
| Burst Pressure | 30000 PSI |
| Factory Part Number | 4EAF4 |
| Hex | 1-1/4" |
| Length | 2.20" |
| Material | Steel |
| Maximum OD | 1.62" |
| Maximum Operating Pressure | 10000 PSI |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |
| Thread | Female NPTF |
| Thread Size | 1/2"-14 |
| Weight Lb | 0.6400 |