


DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER WITH LOCKING SLEEVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/13/2026 02:20 PM

SKU

: 4903

BRAND

: DIXON VALVE

MODEL

: 4EF4-S-LS

Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Machined components are manufactured using 303 stainless steel bar stock. Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|---------------------------------|
| Body Size | 1/2" |
| Burst Pressure | 12,000 PSI (827 Bar) |
| Factory Part Number | 4EF4-S-LS |
| Female Thread | NPTF |
| Female Thread Size | 1/2"-14 |
| Hex | 1-1/8" |
| Length | 1.86 (47.2mm) |
| Material | 303 Stainless Steel |
| Maximum OD | 1.34 (34.0mm) |
| Maximum Operating Pressure | 3,000 PSI (207 Bar) |
| Seal | Buna-N |
| Temperature Range | -40°F - +250°F (-40°C - +121°C) |
| Weight Lb | 0.3500 |