

## DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/09/2026 04:41 AM

SKU  
: 4905

BRAND  
: DIXON VALVE

MODEL  
: 4EM4-S

### Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

### Construction:

Machined components are manufactured using 303 stainless steel bar stock. Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

### Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

### Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	1/2"
<b>Burst Pressure</b>	12,000 PSI (827 Bar)
<b>Factory Part Number</b>	4EM4-S
<b>Male Thread</b>	NPTF
<b>Male Thread Size</b>	1/2"-14
<b>Material</b>	303 Stainless Steel
<b>Maximum Operating Pressure</b>	3,000 PSI (207 Bar)
<b>Temperature Range</b>	-40°F - +250°F (-40°C - +121°C)
<b>Weight Lb</b>	0.3400