

DIX-LOCK® N-SERIES BOWES INTERCHANGE SEAL



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/10/2026 07:43 AM

SKU
: 22623

BRAND
: DIXON VALVE

MODEL
: 4N-SKIT

Specifications:
Conforms to MIL-C-3486 and A-A-50431A standards

Construction:
Pneumatically Energized Nitrile Seal

Compatibility & Interchange Data:
Bowes Interchange Bayonet Style
Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald Quick-Action, Campbell Single-Lock

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	4N-SKIT
Material	Nitrile
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Weight Lb	0.0045