

## DIX-LOCK® N-SERIES INTERCHANGE FEMALE HEAD X MALE THREADED END COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/22/2026 09:46 PM

SKU  
: 22636

BRAND  
: DIXON VALVE

MODEL  
: 4NBM6-B

#### Specifications:

Rated pressure for connected Brass Coupler & Brass Plug: 300 PSI (20 Bar)  
Maximum Working and 8,200 PSI (865 Bar) Burst  
Conforms to MIL-C-3486 and A-A-50431A standards

#### Construction:

Machined components are manufactured using solid bar stock.  
Nitrile (Buna-N) seals standard

#### Available Options:

Additional seal options available, contact Dixon  
316 stainless steel available in some versions upon request, contact Dixon

#### Compatibility & Interchange Data:

Bowes Interchange Bayonet Style  
Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald  
Quick-Action, Campbell Single-Lock

#### Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	4NBM6-B
<b>Hex</b>	1-3/8"
<b>Length</b>	1.85" (47.0mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	1.50" (38.1mm)
<b>Pressure Rating</b>	See Product Details
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	BSPT
<b>Thread Size</b>	3/4"
<b>Weight Lb</b>	0.3800