

## DIX-LOCK® N-SERIES BOWES INTERCHANGE FEMALE THREADED COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/10/2026 06:51 AM

SKU  
: 22646

BRAND  
: DIXON VALVE

MODEL  
: 4NF6-SS

Specifications:  
Conforms to MIL-C-3486 and A-A-50431A standards

Construction:  
Machined components are manufactured using solid bar stock.  
Nitrile (Buna-N) seals standard

Available Options:  
Additional seal options available, contact Dixon

Compatibility & Interchange Data:  
Bowes Interchange Bayonet Style  
Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald  
Quick-Action, Campbell Single-Lock

Safety notes:  
It is important to be safe when installing quick disconnect couplings into a  
pneumatic circuit. Never install a pneumatic coupling directly into an air tool,  
use a piece of hose that is at least 18" long, between the tool and the  
coupling, to prevent damage to the coupling. To protect the operator, safety  
devices, such as a safety check valve and safety cable should be installed in  
case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	4NF6-SS
<b>Hex</b>	1-3/8"
<b>Length</b>	1.63" (41.4mm)
<b>Material</b>	316 Stainless Steel
<b>Maximum OD</b>	1.54" (39.1mm)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	NPTF
<b>Thread Size</b>	3/4"