

**DIX-LOCK® N-SERIES
INTERCHANGE FEMALE HEAD
X MALE THREADED END
COUPLER**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/10/2026 09:14 AM

SKU
: 22660

BRAND
: DIXON VALVE

MODEL
: 4NM8-SS

Specifications:
Conforms to MIL-C-3486 and A-A-50431A standards

Construction:
Machined components are manufactured using solid bar stock.
Nitrile (Buna-N) seals standard

Available Options:
Additional seal options available, contact Dixon

Compatibility & Interchange Data:
Bowes Interchange Bayonet Style
Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald
Quick-Action, Campbell Single-Lock

Safety notes:
It is important to be safe when installing quick disconnect couplings into a
pneumatic circuit. Never install a pneumatic coupling directly into an air tool,
use a piece of hose that is at least 18" long, between the tool and the
coupling, to prevent damage to the coupling. To protect the operator, safety
devices, such as a safety check valve and safety cable should be installed in
case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	4NM8-SS
Material	316 Stainless Steel
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	1"
Weight Lb	0.5000