

DIX-LOCK® N-SERIES INTERCHANGE FEMALE HEAD COUPLER STANDARD HOSE BARB



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 09:46 PM

SKU

: 22676

BRAND

: DIXON VALVE

MODEL

: 4NS8-SS

Specifications:

Conforms to MIL-C-3486 and A-A-50431A standards

Construction:

Machined components are manufactured using solid bar stock.

Nitrile (Buna-N) seals standard

Available Options:

Additional seal options available, contact Dixon

Staked ferrule option available, contact Dixon

Compatibility & Interchange Data:

Bowes Interchange Bayonet Style

Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald

Quick-Action, Campbell Single-Lock

Safety notes:

Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.

Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death.

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	4NS8-SS
Hose ID	1"
Length	3.49" (88.7mm)
Material	316 Stainless Steel
Maximum OD	1.33" (33.8mm)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Weight Lb	0.6000