

DUAL-LOCK P-SERIES THOR INTERCHANGE MALE THREAD COUPLER WITH KNURLED FLANGED SLEEVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/10/2026 12:33 PM

SKU
: 4961

BRAND
: DIXON VALVE

MODEL
: 4PM3-FS

Construction:

Machined components are manufactured using solid bar stock.

Nitrile (Buna-N) seals are standard

Stainless steel retaining ring and spring maximize corrosion resistance and extend service life on the 1 piece sleeve. 2-Piece Sleeve has a phosphor bronze spring.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Thor Finger-Lock Interchange

Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	2600 PSI (180 bar)
Factory Part Number	4PM3-FS
Material	Steel
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	3/8"
Weight Lb	0.6200