

15K THREADED COUPLER



DATE
: 05/21/2026 02:33 PM

SKU
: 4995

BRAND
: DIXON VALVE

MODEL
: 4TDF4-SS

Construction:

Machined components are manufactured using 316 stainless steel bar stock
Stainless steel retaining ring to maximize corrosion resistance and extend service life

Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

Compatibility & Interchange Data:

Jet Stream Screw Type
Spir Star CQD Series, DNP CRS Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	4TDF4-SS
Length	2.57"
Material	316L Stainless Steel
Maximum OD	1.85"
Maximum Operating Pressure	15,000 PSI
Temperature Range	-40°F - 250°F (-40°C - 121°C)
Thread	Female NPTF
Thread Size	1/2"-14

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Weight Lb

1.0500