

## 15K THREADED COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 12:43 AM

SKU  
: 4995

BRAND  
: DIXON VALVE

MODEL  
: 4TDF4-SS

**Construction:**

Machined components are manufactured using 316 stainless steel bar stock  
Stainless steel retaining ring to maximize corrosion resistance and extend service life

Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

**Compatibility & Interchange Data:**

Jet Stream Screw Type

Spir Star CQD Series, DNP CRS Series

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/2"
<b>Factory Part Number</b>	4TDF4-SS
<b>Length</b>	2.57"
<b>Material</b>	316L Stainless Steel
<b>Maximum OD</b>	1.85"
<b>Maximum Operating Pressure</b>	15,000 PSI
<b>Temperature Range</b>	-40°F - 250°F (-40°C - 121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1/2"-14

**TECHNICAL SPECIFICATIONS**

**Weight Lb**

1.0500