


**CAM & GROOVE ADAPTER
BUTT WELD TO SCHEDULE 40
PIPE/SOCKET WELD TO
NOMINAL TUBING**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/21/2026 11:45 PM

SKU
: 5137

BRAND
: DIXON VALVE

MODEL
: 500AWBPSTAL

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
No standard exists for the 5" fittings, and generally does not interchange with other manufacturers.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Final weld preparation, as with all weld fittings, is the responsibility of the welder.

Line drawings are for reference only. Consult Dixon for specific dimensions.

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F (21°C) with a standard Buna-N seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	356T6 Aluminum
Maximum Operating Pressure	75 PSI
Factory Part Number	500AWBPSTAL
Size	5"
Weight Lb	1.6600