

DIXON® CAM & GROOVE COUPLER SOCKET WELD TO SCHEDULE 40 PIPE



DATE
: 06/10/2026 03:34 AM

SKU
: 5145

BRAND
: DIXON VALVE

MODEL
: 500DWSPSS

Applications:

Designed for use with liquids, consult Dixon for specific recommendations

Specifications:

No standard exists for the 5" fittings, and generally does not interchange with other manufacturers.

Available Options:

Boss-Lock versions are also available. Consult Dixon for pricing and availability.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Final weld preparation, as with all weld fittings, is the responsibility of the welder.

Line drawings are for reference only. Consult Dixon for specific dimensions.

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Material	316 Stainless Steel
Maximum Operating Pressure	75 PSI
Factory Part Number	500DWSPSS
Size	5"
Weight Lb	9.3800