TTMA FLANGED SIGHT FLOW INDICATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/02/2026 06:49 PM

SKU
: 5244

BRAND
: DIXON VALVE

MODEL
: 5201-SFI-3

Applications:
TTMA sight flow indicators are often used between the API valve and tanker piping, allowing the operator to see fuel flow to or from tank. They can be used in many other applications where a visual of liquid flow is required.

Use:
Allows for visual identification of fuel grade prior to opening the valve
Works with tank truck flanged butterfly valves found on gasoline trucks

Features:
Maximum flange bolt torque is 200 in-lb. (inch pounds)

Construction:
Aluminum body
Acrylic sight flow
Baylast™ seals

Safety notes:
Due to the proprietary blending of petroleum products, Dixon recommends that the thermoplastic tubing and the gaskets be immersion tested in the product to be handled to ensure compatibility
Not compatible with crude oil.
Maximum flange bolt torque is 200 in-lb (inch pounds)
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Flange Size	3" TTMA
Fuel Compatability	Gasoline and diesel, up to E100 and B100 biofuels
ID	3-1/2"
Material	Aluminum
Factory Part Number	5201-SFI-3
Pressure Rating	150 PSI
Seal	Baylast?
Weight Lb	1.8770
Width	3-1/4"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us