

**TTMA FLANGED SIGHT FLOW
INDICATOR**



DATE
: 04/23/2026 12:44 AM

SKU
: 5243

BRAND
: DIXON VALVE

MODEL
: 5201-SFI

Use:

Allows for visual identification of fuel grade prior to opening the valve
Works with tank truck flanged butterfly valves found on gasoline trucks
Larger ID 4-3/8" flow indicator allows tank truck flanged butterfly valves to connect to either end of the indicator

Construction:

Durable cast aluminum housing
Baylast™ O-ring
Steel retainer ring

Safety notes:

Due to the proprietary blending of petroleum products, Dixon recommends that the thermoplastic tubing and the gaskets be immersion tested in the product to be handled to ensure compatibility
Not compatible with crude oil.
Maximum flange bolt torque is 200 in-lb (inch pounds)
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Flange Size	4" TTMA
Fuel Compatability	Gasoline and diesel, up to E100 and B100 biofuels
ID	4-3/8"
Material	Aluminum
Factory Part Number	5201-SFI
Pressure Rating	150 PSI

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Seal	Baylast?
Weight Lb	2.1400
Width	3-1/4"