

API LOAD/UNLOAD VALVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/20/2026 05:28 PM

SKU

: 5275

BRAND

: DIXON VALVE

MODEL

: 5204SFI-P

Applications:

Used for bottom loading and unloading of petroleum tankers, Load/unload valve permits both terminal loading, and fuel unloading through the valve.

Specifications:

Manufactured to American Petroleum Institute standard API RP-1004, which allows for positive connection to drop adapters and rack couplers such as the Dixon Bayco 5300/5400 series rack coupler.

Features:

Unique fluid flow sight level

Ergonomically curved handle operates on a short 62° degree stroke

Any required maintenance is simplified, Dixon Bayco API Valves can be completely rebuilt without the need to remove the valve from the tanker

Nose ring is anodized hard coat aluminum, which in most applications will provide years of trouble free service. Nose ring can be rotated to provide a fresh connection service.

Construction:

Aluminum body with anodized hard coat aluminum nose ring and stainless steel hardware

Fixed aluminum handle

Inline Acrylic full body sight glass

Baylast™ seals

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Fuel Compatability	Gasoline and diesel, and up to E100 and B100 biofuels
Length	8.81"
Material	Aluminum
Factory Part Number	5204SFI-P
Seal	Baylast?
Style	Fixed handle, inline full body sight glass, drilled/tapped boss
Weight Lb	12.5200