


LOK-ON FEMALE SWIVEL GARDEN HOSE FITTING



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 08:39 AM

SKU
: 5390

BRAND
: DIXON VALVE

MODEL
: 5741212C

Specifications:
Number of Barbs: 3
Barb Length: 1.48"

Features:
Washer included, part # 5911212W

Installation

Assembly Instructions:

1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions

Disassembly instructions:

1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	5741212C
Component Material	Yellow Plastic Cap
Weight Lb	0.1350
Hex	1-3/16"
Hose ID	3/4"
Length	2.25"
Material	Brass
Pressure Rating	150 PSI
Temperature Range	+34°F to +150°F
Thread	GHT
Thread Size	3/4"-11-1/2