

## DIXON® CAM & GROOVE TYPE B COUPLER X MALE NPT



DATE  
: 06/10/2026 02:10 PM

SKU  
: 5538

BRAND  
: DIXON VALVE

MODEL  
: 600-B-AL

Applications:  
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:  
Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Features:  
Precision machined to rigid tolerances  
Stainless pins will not rust or bind, providing great strength and safety  
Recess holds gasket firmly in place- ensures proper placement

Construction:  
Buna-N gasket  
Durable stainless steel cam arm pins

Available Options:  
Other gasket types are available, contact Dixon.

How it works:  
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.  
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:  
Under no circumstances should cam and groove couplings be used for compressed air or steam service!  
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Material</b>	356T6 Aluminum
<b>Maximum Operating Pressure</b>	75 PSI
<b>Factory Part Number</b>	600-B-AL
<b>Seal</b>	Buna-N
<b>Size</b>	6"
<b>Weight Lb</b>	4.2200