

## DIXON® CAM & GROOVE COUPLER X 150# FLANGE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 01:55 AM

SKU  
: 5551

BRAND  
: DIXON VALVE

MODEL  
: 600-DL-SS

Applications:  
Designed for use with liquids, consult Dixon for specific recommendations

Use:  
Flanges are designed to mate with #150 flange

Specifications:  
Produced to interchange with all product produced to Commercial Item  
Description A-A-59326D

Construction:  
Flange has raised face

How it works:  
To make a connection, simply slide the adapter into the coupler and with  
normal hand pressure, press the cam levers down.  
Uncoupling is as quick and simple as coupling. Just lift the cam arms and  
remove the adapter.

Safety notes:  
Under no circumstances should cam and groove couplings be used for  
compressed air or steam service!  
Pressure rating recommendations are based on the use of mating Dixon  
fittings at ambient temperature 70°F with a standard seal installed. For use at  
elevated temperature or other unusual operating conditions, consult Dixon.  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	600-DL-SS
<b>Material</b>	316 Stainless Steel
<b>Maximum Operating Pressure</b>	75 PSI
<b>Seal</b>	Buna-N
<b>Size</b>	6"
<b>Thickness</b>	5/8"
<b>Weight Lb</b>	24.1650