

DIXON® CAM & GROOVE REDUCING COUPLER X ADAPTER (TYPE DA)



DATE
: 05/21/2026 02:37 PM

SKU
: 5632

BRAND
: DIXON VALVE

MODEL
: 6050-DA-AL

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item
Description A-A-59326D

Construction:
Buna-N gasket

Available Options:
Other gasket types are available, contact Dixon.

How it works:
To make a connection, simply slide the adapter into the coupler and with
normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and
remove the adapter.

Note:
In reducing couplings, the coupler is the first size in the part number.

Safety notes:
Under no circumstances should cam and groove couplings be used for
compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon
fittings at ambient temperature 70°F with a standard seal installed. For use at
elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Adapter Size	5" (125mm)
Coupler Size	6" (150mm)
Material	356T6 Aluminum
Maximum Operating Pressure	75 PSI
Factory Part Number	6050-DA-AL
Seal	Buna-N
Weight Lb	5.0900