

## COMPRESSION ACETAL SLEEVE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 03:51 AM

SKU

: 22729

BRAND

: DIXON VALVE

MODEL

: 60PT-04

### Applications:

Use with copper, aluminum and thermoplastic tubing.

Manufactured for low and medium pressure tubing connection work where excessive vibration or tube movement is not involved.

### Use:

Acetal sleeves allow for standard compression fittings to be used with industrial grades of thermoplastic tubing.

### Specifications:

Underwriter's Laboratories listed for flammable liquid

SAE J-512

ASA

### Installation

No flaring, soldering or other preparation of tubing necessary to assemble

Slide nut, then sleeve onto tubing. The thread end of the nut must face out.

Insert tube into the fitting. Be sure the tube is bottomed on the fitting shoulder.

Assemble nut to body, and tighten hand-tight. Then follow the number of appropriate wrench turns for the given size.

### Safety notes:

Not recommended for steel tubing

Not recommended for applications using gaseous media.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	60PT-04
<b>Length</b>	.19"
<b>Material</b>	Acetal
<b>Tube Size</b>	1/4"
<b>Weight Lb</b>	0.0003