

AIR BRAKE BULKHEAD UNION 62NFBH



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 01:55 AM

SKU
: 5788

BRAND
: DIXON VALVE

MODEL
: 62NFBH10

Applications:
Designed for use in air brake systems or cab controls

Use:
Utilize ribbed sleeve for compression and positive grip
Compatible tubing: SAE J844 type A and B

Specifications:
Meets D.O.T FMVSS 571.106 and SAE J246

Features:
Positive grip

Construction:
Machined from CA260, CA345 or CA377 brass

Installation
Cut tubing squarely- maximum of 15° angle allowable.
Check that port or mating part is clean and free of debris.
Insert tubing into fittings until it bottoms on seat.
Tighten nut with wrench until one thread remains visible on the fittings body;
(this will allow for a number of remakes) or, the nut should be screwed down
finger tight, then wrench-tightened according to the tube size used.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	62NFBH10
Flow	.137"
Hex	B: 15/16", C: 1"
Length	3.04"
Material	Brass
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Thread	Straight
Thread Size	13/16"-18
Tube Size	5/8"
Weight Lb	0.2000
Working Pressure	150 PSI