

## AIR BRAKE INSERT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/21/2026 04:49 PM

SKU

: 5846

BRAND

: DIXON VALVE

MODEL

: 63NAB8

Applications:

Designed for use in air brake systems or cab controls

Use:

Utilize ribbed sleeve for compression and positive grip

Compatible tubing: SAE J844 type A and B

Specifications:

Meets D.O.T FMVSS 571.106 and SAE J246

Features:

Positive grip

Construction:

302/304 Stainless Steel

Installation

Cut tubing squarely- maximum of 15° angle allowable.

Check that port or mating part is clean and free of debris.

Insert tubing into fittings until it bottoms on seat.

Tighten nut with wrench until one thread remains visible on the fittings body; (this will allow for a number of remakes) or, the nut should be screwed down finger tight, then wrench-tightened according to the tube size used.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	63NAB8
<b>Length</b>	.81"
<b>Material</b>	302/304 Stainless Steel
<b>OD</b>	.370"
<b>Temperature Range</b>	-40°F to 200°F (-40°C to 93°C)
<b>Tube Size</b>	1/2"
<b>Weight Lb</b>	0.0040
<b>Working Pressure</b>	150 PSI