

## PUSH-IN UNION TEE



DATE  
: 07/11/2026 07:56 PM

SKU  
: 5918

BRAND  
: DIXON VALVE

MODEL  
: 645

**Use:**

Suitable for vacuum service

Working pressure: suitable for use up to the maximum working pressure of the plastic tubing used.

**Features:**

Positive seal: no leaks, after tubing is inserted, seal is made

Secure tube retention: pulling on tubing only serves to tighten the connection

Full flow design provides up to 60% more flow than conventional fittings with internal tube supports.

**Installation**

Saves up to 75% of assembly time versus the standard compression fittings.

Quick connect: simply push tubing in, no tools required.

Quick disconnect: hold two fingers on insert and pull tubing out, no tools required.

Reusable: connect and disconnect numerous times

**Safety notes:**

Fittings are suitable for use up to the maximum working pressure of the plastic tubing used

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	645
<b>Material</b>	Forged Brass
<b>Temperature Range</b>	-10°F to 200°F (-23°C to 93°C)
<b>Tube OD</b>	5/32"
<b>Weight Lb</b>	0.0400