

6500 SERIES SELF-LOCKING DROP ELBOW



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 01:29 AM

SKU

: 6029

BRAND

: DIXON VALVE

MODEL

: 6530A

Features:

Ground clearance: 9 1/2"

Most parts are common through the Bayco elbow line, making any necessary maintenance a breeze.

Grease nipple enables the greasing of the lever stem, and Acetal bushings help keep everything moving smoothly, even in the harshest of conditions.

Bolt on inlets allow the inlet to be changed without having to worry about galling of threaded inlets.

Handle lever enables the operator to easily and positively engage the solid bronze locking arms on to the underground adapter.

Heavy duty bolt on arm attachment plate increases the strength of the lever pivot. There are no impact susceptible pivot bolts or casting bosses to break.

Arm hinge points use a double yoke design, which increases the arm strength. Built in heavy duty, locking mechanism prevents accidental elbow disconnections while the elbow is in service. No need for the operator to engage the locking mechanism, just move the handle to the closed position and the lock automatically engages. Releasing the lock is equally as easy, just gripping the handle and lifting. The locking mechanism has lots of free clearance so will not be affected by dirt, ice or snow. (Elbow disconnections can occur on other elbow designs, from either operators bumping the release mechanism, or from a hydraulic surge when the underground storage tank overfill valve slams shut.

Ergonomic handle can be mounted on either side of the elbow.

Construction:

Rugged modular cast aluminum construction

Solid bronze locking arms

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	3" tight fill elbow, 4" adapter
Fuel Compatability	Biofuel compatible up to E100 (100% Ethanol) and B20 (20% Bio Diesel)
Height	15"
Inlet	4" Adapter
Material	Bushing: acetal
Factory Part Number	6530A
Style	Standard Height
Weight Lb	15.5800