

## PUSH-IN FEMALE CONNECTOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/24/2026 05:06 AM

SKU  
: 6059

BRAND  
: DIXON VALVE

MODEL  
: 665X4

### Use:

Suitable for vacuum service

Working pressure: suitable for use up to the maximum working pressure of the plastic tubing used.

### Features:

Positive seal: no leaks, after tubing is inserted, seal is made

Secure tube retention: pulling on tubing only serves to tighten the connection

Full flow design provides up to 60% more flow than conventional fittings with internal tube supports.

### Installation

Saves up to 75% of assembly time versus the standard compression fittings.

Quick connect: simply push tubing in, no tools required.

Quick disconnect: hold two fingers on insert and pull tubing out, no tools required.

Reusable: connect and disconnect numerous times

### Safety notes:

Fittings are suitable for use up to the maximum working pressure of the plastic tubing used

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                            |                                |
|----------------------------|--------------------------------|
| <b>Factory Part Number</b> | 665X4                          |
| <b>Female Thread</b>       | NPTF                           |
| <b>Female Thread Size</b>  | 1/8"                           |
| <b>Material</b>            | Forged Brass                   |
| <b>Temperature Range</b>   | -10°F to 200°F (-23°C to 93°C) |
| <b>Tube OD</b>             | 5/32"                          |
| <b>Weight Lb</b>           | 0.0415                         |