


**DQC CVV-SERIES EUROPEAN  
INTERCHANGE FEMALE  
COUPLER**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 10:49 PM

SKU  
: 6187

BRAND  
: DIXON VALVE

MODEL  
: 6CVVFM2215

Construction:

Machined components are manufactured using solid bar stock

Steel retaining rings and springs maximize service life in rugged environments.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:

European Screw-Together Interchange

Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Note:

Threaded sleeves enable easy connection and disconnection while system is under residual pressure only.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

|                            |                      |
|----------------------------|----------------------|
| <b>Body Size</b>           | 3/4"                 |
| <b>Burst Pressure</b>      | 23200 PSI (1600 Bar) |
| <b>Factory Part Number</b> | 6CVVFM2215           |
| <b>Hex</b>                 | 36mm                 |
| <b>Length</b>              | 3.15" (80.0mm)       |
| <b>Material</b>            | Steel                |
| <b>Maximum OD</b>          | 1.89" (48.0mm)       |

## TECHNICAL SPECIFICATIONS

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>Maximum Operating Pressure</b> | 5800 PSI (400 Bar)                |
| <b>Temperature Range</b>          | -40°F to +250°F (-40°C to +121°C) |
| <b>Thread</b>                     | Female Metric                     |
| <b>Thread Size</b>                | M22X1.5                           |
| <b>Weight Lb</b>                  | 1.0800                            |