

PUSH-IN FEMALE ELBOW



DATE
: 07/11/2026 03:13 PM

SKU
: 6280

BRAND
: DIXON VALVE

MODEL
: 708X8

Use:

Suitable for vacuum service

Working pressure: suitable for use up to the maximum working pressure of the plastic tubing used.

Features:

Positive seal: no leaks, after tubing is inserted, seal is made

Secure tube retention: pulling on tubing only serves to tighten the connection

Full flow design provides up to 60% more flow than conventional fittings with internal tube supports.

Installation

Saves up to 75% of assembly time versus the standard compression fittings.

Quick connect: simply push tubing in, no tools required.

Quick disconnect: hold two fingers on insert and pull tubing out, no tools required.

Reusable: connect and disconnect numerous times

Safety notes:

Fittings are suitable for use up to the maximum working pressure of the plastic tubing used

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	708X8
Female Thread	NPTF
Female Thread Size	1/4"
Material	Forged Brass
Temperature Range	-10°F to 200°F (-23°C to 93°C)
Tube OD	1/4"
Weight Lb	0.0900