

DIXON® CAM & GROOVE REDUCING COUPLER X ADAPTER (TYPE DA)



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/10/2026 08:40 AM

SKU

: 6483

BRAND

: DIXON VALVE

MODEL

: 8060-DA-AL

Applications:

Designed for use with liquids, consult Dixon for specific recommendations

Specifications:

No standard exists for the 8" fittings, and generally does not interchange with other manufacturers.

Construction:

Buna-N gasket

Produced as a welded fabrication

Available Options:

Other gasket types are available, contact Dixon.

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Note:

In reducing couplings, the coupler is the first size in the part number.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

The 8" coupler only interchanges with Dixon Andrews type adapters

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Adapter Size	6" (150mm)
Coupler Size	8" (200mm)
Material	356T6 Aluminum
Maximum Operating Pressure	50 PSI
Factory Part Number	8060-DA-AL
Seal	Buna-N
Weight Lb	12.9000